



NEOCOLORI

Colori dell'Italia



SPECIFICATIONS AND FIELDS OF EMPLOYMENT

Bellagio is decorative wall finish made from special acrylic emulsions highly resistant to fungi and bacteria. Bellagio becomes fully washable two weeks after application. It is non-toxic VOC (<17) L/A 200g/l (2010). It can be used in system with **NEOPRO primer A** and **NEOPRO** durable paint.

Thinner: Water

Drying time: touch dry 2 hours, 6 to 8 between coats

Yield: 8 to 10 m² per 1 lit

Flammability: Not flammable

S46 If swallowed, immediately contact a doctor and show him the packaging and labeling


COMPOSITION

Bellagio is special acrylic emulsion which contains natural and synthetic biostatic micas, additives, organic and inorganic pigments.

METHODS OF APPLICATION

Surface preparation:

Surface must be smooth and dust free. If you have imperfection you can plaster with **NEO rasatura** (according to the thickness) and apply one coat of **NEOPRO primer A**, properly diluted with water in a ratio of 1:5 to 1:10, according to the support absorption degree. Let the support dry for at least 4 hours and apply two coats of **NEOPRO** interior paint - based paint at 4\5 - hour intervals.



APPLICATION

The application of Bellagio is very simple and fast. There are 3 different methods of application as follows:

Effetto Spatolato:

Spread one coat of Bellagio with the special Bellagio plastic trowel with a thickness of about 0.5 - 1 mm and leave to dry for about 6 to 8 hours. Apply a second coat of Bellagio in small areas at about 1 m² go over the surface in criss - cross directions continue with the same procedure until you have completed the entire surface.

Effetto Damascato:

Spread one coat of Bellagio with the special Bellagio plastic trowel with a thickness of about 0.5 - 1 mm and leave to dry for about 6 to 8 hours. Apply a second coat of Bellagio and even the surface, when dry apply some more Bellagio with Bellagio Trowel or with a paint brush and apply to the entire surface, tamping the surface in irregular directions, wait for about 5 minutes and then gently go over the surface with a clean Bellagio plastic trowel.

Effetto Broccato:

Spread one coat of Bellagio with the special Bellagio plastic trowel with a thickness of about 0.5 - 1 mm and leave to dry for about 6 to 8 hours. Apply a second coat of Bellagio it should be thicker than the first coat covering about 1 m² at a time and go over the surface with a special Bellagio plastic trowel in irregular circular directions continue with the same procedure until you have completed the entire surface.

TECHNICAL DATA:

Specific weight: 1,300 kg/lit +/- 50 gr/lit

Colors: to be chosen from the **NEOCOLORI** design color card

Viscosity: thixotropic paste

Yield: 8-10 m²/lit

Dilution: ready for use

Package: Bellagio is available in 1 lit and 4 lit or bigger package for projects

Drying: touch dry after 2 hours, completely dry after 24 hours at 20°C

Application: apply with a special Bellagio plastic trowel or stainless-steel spatula

Preservation: 24 months in the intact package, away from temperature changes
